



- Customizable
- Absorbs noise
- Rugged and durable
- Available in rolls

## SONEXcurtain™ Quilted Absorber (QA) Product Information

SONEXcurtains QA combines the sound absorbing features of willtec® foam with the advantages of durable, cleanable and abrasion-resistant facings. These panels withstand a wide range of temperature limits and are unaffected by humidity, dust, dirt, oils and most chemicals.

SONEXcurtains QA can be custom manufactured to integrate as a complete acoustical enclosure system giving access to machines or work cells. They are also available in 25' and 50' rolls with finished or unfinished edges.

SONEXcurtains QA are easy to install. Curtain hardware, hanging mechanisms and configuration options include clear vinyl windows, grommets, hook and loop fasteners, doors and sliding tracks. The standard facing material is a vinyl-coated fabric in grey, white, tan or black.

### Applications

- Line inside of welding booths with panels made with silicone-facing option
- Add absorption to pre-existing walls or partitions
- Adhere to walls to reduce general noise level in rooms or buildings
- Install as ceiling baffles with hanging mechanisms
- Improve communication in high-traffic areas and corridors
- Reduce reverberation in large manufacturing environments
- Suitable for some outdoor applications

### SONEXcurtain QA Product Specifications

Construction	Single or double layer quilted willtec acoustical foam
Facing Material	Standard: Vinyl-coated fabric (grey, white, tan, black) Optional: Hi-temp silicone-coated fabric, decorative cloth or non-woven porous scrim fabric
Surface Pattern	Diamond-quilted or straight-stitch patterns
Density	willtec foam: 0.7 lb./cubic ft.
Flammability	Class 1 per ASTM E84
Flame Spread	25
Smoke Density	57

### Sound Absorption Coefficients

Type G Mounting ASTM C423-90							
	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	NRC
QA-1	0.09	0.28	0.74	0.58	0.38	0.25	0.50
QA-2	0.14	0.55	0.96	0.73	0.36	0.25	0.65

3800 Washington Avenue North  
Minneapolis, MN 55412  
Toll-Free 1-800-662-0032  
sales@pinta-acoustic.com  
www.pinta-acoustic.com